

TITLE :	TECHNICAL DATA SHEET FOR FIRE HOSE WITH COUPLINGS		DOC NO.	MMLH/FPS/06	
PACKAGE:	FIRE PROTECTION SYSTEM	REV.	0	DATE:	12.10.2017.
PROJECT:	MMLH VIZAG	SHEET	1	OF	1
1.0	Manufacturer	:	NEWAGE / Fire Shield / BRG / CRC / GEI / Equivalent approved make		
2	Confirms to IS Code	:	IS:14933-2001 together with end GM couplings (ISI Marked). The general design and construction of instantaneous end couplings, shall comply to IS: 903 (latest revision)		
3	Type	:	As per IS:14933-2001		
4	Quantity	:	As per Engg.		
5	Burst Pressure	:	38 Kg/cm ²		
6	Operating Pressure	:	12 Kg/cm ²		
7	Proof Pressure	:	22 Kg/cm ² shall be conducted along with coupling duly bound on hose pipe by GI Wire		
8	Size	:	63 mm x 15 M long		
9	Type of Coupling	:	Instantaneous as per IS:14933-2001		
10	Hoses shall have ISI certification marks	:	Yes		
11	Material of Hose	:	Rubber lined, woven jacketed type conforming to IS: 636 Type A		
11.1	Material of hose coupling	:	SS		
12	Whether approved by TAC	:	Yes		
13	Marking	:	IS:14933-2001 Year of Manufacturer Manufacturers name of trademark		