



**Balmer Lawrie & Co. Ltd.**

## USAGE GUIDE - PROPERTIES IMPARTED BALSYN<sup>®</sup> RESIN & HIGH PERFORMANCE ACRYLIC SYNTANS

BL PRODUCTS	Rechroming	Fullnes	Dye depth	Surface feel	Retanning	Body	Inner softness	Grain tightness	Surface feel	Buffability	Dye depth
ACR 40	-	-	-	-	-	VG	VG	VG	VG	VG	VG
MR 50	-	-	-	-	-	G	VG	G	VG	VG	VG
MR 70	-	-	-	-	-	G	VG	G	VG	VG	VG
MAR	-	-	-	-	-	E	G	VG	G	VG	VG
ACR 1	-	-	-	-	-	G	VG	G	G	G	G
MAR (V)	-	-	-	-	-	VG	G	VG	VG	VG	VG
MAR SPL	RECHROMING	-	-	-	RETANNING	E	G	VG	VG	G	VG
BB 17	RECHROMING	-	-	-	RETANNING	G	VG	G	VG	VG	VG
MM	RECHROMING	-	-	-	RETANNING	VG	VG	VG	VG	E	G
B 70	RECHROMING	-	-	-	RETANNING	G	VG	G	VG	E	VG
MP 1	-	-	-	-	-	G	VG	G	G	G	G
MP 30	-	-	-	-	-	VG	G	G	VG	G	G
SAR	-	VG	VG	VG	-	VG	E	VG	VG	G	VG
SRM	-	G	G	G	-	G	VG	G	G	-	G
KSK (B)	-	VG	VG	VG	-	VG	E	E	VG	G	VG
KSK	-	VG	VG	VG	-	VG	E	E	VG	G	VG

### LEGEND

(E) – EXCELLENT

(VG) – VERY GOOD

(G) – GOOD

### NOTE :

1. Properties mentioned above are relative characteristics. This chart may be used for general guidance only.

<sup>®</sup> Trademark Registration

*Technique*  
October, 2009

All data and recommendations given in this document are for guidance only and we cannot be held responsible in any way whatever.