



Balmer Lawrie & Co. Ltd.

USAGE GUIDE - PROPERTIES IMPARTED BALSYN® REPLACEMENT SYNTAN

BALSYN® PRODUCTS	PF18I	PFKI	RD	RA10	DR	DRW	S	RS	DNP	DNF
RETANNING (3-6%)										
BODY	VG	G	E	VG	E	VG	VG	VG	VG	VG
MELLOWNESS	G	G	G	E	E	E	G	VG	VG	VG
GRAIN FLATNESS	VG	VG	VG	E	E	VG	VG	VG	VG	VG
DYEABILITY	VG	VG	VG	VG	VG	VG	E	VG	E	E
BUFFABILITY	G	G	VG	G	VG	VG	E	G	G	G
RECHROMING (1-2%)										
FULLNESS	VG	VG	E	G	E	VG	G	VG	VG	VG
DYE DEPTH	G	G	E	VG	G	G	E	G	E	E
SURFACE FEEL	G	G	G	G	E	VG	G	G	G	G
EI TANNING (1-3%)										
BODY	VG	VG	E	VG	E	VG	G	G	G	G
LEVELLING	VG	VG	G	G	VG	E	E	G	G	G
PENETRATION	E	E	G	VG	E	E	VG	VG	VG	VG
SLUDGE REDUCTION	E	E	G	VG	E	E	VG	G	G	G

LEGEND

(E) – EXCELLENT (VG)- VERY GOOD (G) – GOOD

NOTE :

1. Properties mentioned above are relative characteristics. This chart may be used for general guidance only.

® Trademark Registration

Technique
October, 2009

All data and recommendations given in this document are for guidance only and we cannot be held responsible in any way whatever.