

BALMOL® GP60

Characteristics : Softening and dispersing agent based on sulpho succinates

pH of 10 % solution : 6.0 - 7.0

Appearance : Light Yellow to Dark Yellow Clear Liquid

Properties Imparted : **Balmol GP60** is a specially designed multipurpose product

which can be used at any pH. It emulsifies and distributes the natural fat, thus when used in chrome tanning, it helps in getting even tanning by dispersing the chrome. Balmol GP60 can be

used during Pickling, Tanning, Rechroming, Retanning and Dyeing. It

imparts

• Full electrolyte stability

Good softness to leather when used in pickling/Tanning

• Uniform and deep penetration

 Good gliding action in the drum, reducing rub marks and entangling of the leather

Good distribution of natural fat and avoids the precipitation of grease

Uniform and easier shaving

• Good dyeability and levelling

Application : In Pickling : 0.1-0.5 % on the pelt weight, 15 min before

addition of acid

In Chrome Tanning: 0.1-0.5 % on the pelt weight, 10min after the first

addition of chrome

In Pickling and Chrome Tanning: 0.1-0.5 % on the pelt weight

In Retanning: 2-5% on shaved weight, either with chrome or 10min later.

Subsequently a minimum running time of 60 min.

For E.I Tanning: 0.1-0.5 % on shaved weight, It will disperse the vegetable

extracts that will give good pleasant color to EI leather. For uniform wet back 0.2-0.5 % can be used on crust weight

Safety : A non-hazardous industrial chemical should be handled with normal care.

Any contact with eyes or spillage on skin should be washed thoroughly in

running water.

Storage : This product has 12 months shelf life when stored in original packing in

sealed condition at ambient temperature. Protect from moisture & sunlight. Avoid freezing. **Stir well before use. Close Container tightly**

after use.

Product January 2018